600x600mm Vitrified Tiles





EDITION
JANUARY 2025











ORBIT









ORCHID



CASONA

ASTER





















ITALIAN MARBLE

RETRO



ORCHID






















DC SILVASA

DC TROPICANA








CELICA BROWN

TIDES







EXTREME




















ASTON

**IVORY** 



EXTREME


















MARY GOLD



AUSTIN





ANGEL



MAGIC



LEGNO



GLORY























CELICA BLUE

ARCADIA



ARCADIA
























PEARL WOOD









COAST WOOD



ROYAL FEATHER

WEST WOOD















### **Technical Specification**

600 600 Vitrified Tiles

	CHARACTERISTICS	Requirement as per ISO 13006/EN176 Gr Bla IS 15622:2006	Home Square Value	Test Method				
(A) DIMENSION & SURFACE QUALITY								
	Deviation In Length	± 0.60%	± 0.10%	ISO 10545 Part-2				
1	Deviation In Thickness	± 5.00%	± 3.00%	ISO 10545 Part-2				
	Straightness of Edge	± 0.50%	± 0.10%	ISO 10545 Part-2				
Ĭ	Rectangularity	± 0.60%	± 0.20%	ISO 10545 Part-2				
>	Surface Flatness	± 0.50%	± 0.20%	ISO 10545 Part-2				
++	Glossiness	-	Min. 80% Reflection	Glossmeter				
(B) PHYSICAL & THERMAL PROPERTIES								
<b>S</b> .	Water Absorption % By Wt.	< 0.50%	< 0.50%	ISO 10545 Part-3				
<b>↓</b>	Flexural Strength (MOR) In N/mm²	35 N/mm²	> 40 N/mm²	ISO 10545 Part-4				
	Breaking Strength in N	Min. 1300 N	Min. 2000 N	ISO 10545 Part-4				
0	Resistance to Surface Abrasion	≤ 175mm³	≤ 144mm³	ISO 10545 Part-6				
$\overline{\longleftrightarrow}$	Co-efficient of Liner Thermal Expansion from ambient temp to 100°C (K-1)	≤ 9X10 <sup>-6</sup>	≤ 6X10 <sup>-6</sup>	ISO 10545 Part-8				
İ	Bulk Density (gm/cc)	Min. 2.0	Min. 2.2	ISO 10545 Part-3				
**	Thermal Shock Resistance	Min. 10 Cycles	No Damage	ISO 10545 Part-9				
6	Moisture Expansion in mm/M	Nil	Nil	ISO 10545 Part-10				
	Skid Resistance (Friction Coefficient)	> 0.40	> 0.40	ISO 10545 Part-6				
*	Frost Resistance	Frost Proof	Frost Proof	ISO 10545 Part-9				
**	Moh'S Scratch Hardness	> 6	> 6	EN 101				
(C) CHEMICAL PROPERTIES								
S	Resistance To House hold Chemicals	No Damage	No Damage	ISO 10545 Part-13				
8	Colour Resistance	No Damage	No Damage	DIN 51094				
<u>I</u> R	Stain Resistance	Resistance	Resistance	ISO 10545 Part-14				

<sup>\*\*</sup>Not applicable for structured tiles

## **Packing Details**

Size	Thickness	No. of Tiles / Box	Area / Box	Weight / Box
600x600mm	7.50 mm (approx)	4 pcs	1.44m²	22.0 kg

**DISCLAIMER**: We reserves the right to delete & amend either totally of partially, any of the colours, shapes, sizes, references and other technical specifications contained in this catalogue at any time. The colours shown of tiles in this catalogue are purely illustrative and limited to printing process. Please refer actual sample before final selection. The details of colours, sizes, references should be verified for Typographical errors. SHADE & SIZE VARIATIONS are inherent characteristics of ceramics. NO COMPLIANT SHALL BE ENTERTAINED ON TILES ALREADY LAID/FIXED.





# **Floors** that make you feel like KING

Mfd by : The Home Square LLP

Mktd by: Rooflux Tiles and Sanitary Pvt. Ltd.

#### **ZONAL OFFICE (EAST) – PATNA**

404, GenX Icon, Near Saguna More, Bailey Road, Patna Bihar-801503

#### **ZONAL OFFICE (WEST) – MUMBAI**

B-602, Shankar Tower, Sanpada, Navi Mumbai-400705

#### **ZONAL OFFICE (NORTH) - NEW DELHI**

25, Block-BI, Sewak Park, Uttam Nagar, New Delhi- I 10059

#### **OFFICE (REGD.)**

25, Block-BI, Séwak Park, Uttam Nagar, New Delhi-I 10059

#### **OFFICE (MORBI)**

F31, 1st Floor, B/H Real Plaza, Near Vardhaman Hotel, 8A National Highway, Lalpar, Morbi-363642

- +91 7070706001
- info@thehomesquare.in
- www.thehomesquare.in



Find us at: www.facebook.com/homesquaretiles



Find us at: www.instagram.com/homesquaretiles



www.youtube.com/homesquaretiles

